



SILENT K50 T10

I COMPRESSORI SILENT 2 proposti nelle versioni con motori da 3 a 7,5 kW, questi elettrocompressori presentano le seguenti caratteristiche:

- scheda elettronica di auto diagnosi e comando; ■ contatore;
- manometro con glicerina; ■ polmone smorzante; ■ rubinetto di spurgo;
- ventilazione forzata per l'abbattimento della temperatura interna;
- termostati di controllo della temperatura; ■ valvola di sicurezza;
- elettrovalvola per lo scarico della testa; ■ silenziatore in aspirazione.

SILENT 2 COMPRESSORS, proposed in versions with motors from 3 to 7.5 kW, these electrocompressors have the following features:

- electronic self-diagnosis and control profile; ■ counter;
- pressure gauge with glycerine; ■ damping receiver; ■ drain valve;
- forced ventilation to reduce internal temperature ■ thermostat for temperature control;
- safety valve; ■ solenoid valve for head discharge; ■ silencer for aspiration.

SD = Avviatore stella triangolo/Star delta starter

Prestazioni | Performance

Nome Name	Codice Code	Gruppo Pump	Serbatoio Tank	Potenza Power	Cilindri Cylinder	Press. Max Max press.	Lubrificato Lubricated	N° Giri RPM	Aria Aspirata Air Displacement	Tensione Frequenza Voltage Frequency	Peso Weight	Dimensioni Dimensions	dB (A)	Codice a barre Ean code
			Lt	Hp/kW	n.	bar/PSI			l/min./CFM	Volt/Hz	kg/lbs	LxPxA / WxDxH		
SILENT K30 T5,5	SLOM701SHA	K30	3	5,5/4,0	2	11/160	YES	1000	727/20,5	400/50	168/396,6	850x620x1100	65	8028403011395
SILENT K30 T5,5 SD	SLOM705SHA	K30	3	5,5/4,0	2	11/160	YES	1000	727/20,5	400/50	173/380,6	850x620x1100	65	8028403011401
SILENT K30 T7,5	SLOM801SHA	K30	3	7,5/5,5	2	11/160	YES	1200	827/25,7	400/50	182/400	850x620x1100	65	8028403011418
SILENT K30 T7,5 SD	SLOM805SHA	K30	3	7,5/5,5	2	11/160	YES	1200	827/25,7	400/50	187/411,4	850x620x1100	68	8028403011425
SILENT K50 T10	SMOM901SHA	K50	3	10/7,5	2	11/160	YES	1000	1074/38	400/50	220/484	850x620x1100	68	8028403011432
SILENT K50 T10 SD	SMOM905SHA	K50	3	10/7,5	2	11/160	YES	1000	1074/38	400/50	225/495	850x620x1100	68	8028403011449

Pressione massima | Max pressure 13 bar

SILENT K25 T4	SGOM601SHA201	K25	3	4/3,0	2	13/189	YES	800	330/11,7	400/50	147/323,4	850x620x1100	65	8028403011456
SILENT K25 T4 SD	SGOM605SHA202	K25	3	4/3,0	2	13/189	YES	800	330/11,7	400/50	152/334,4	850x620x1100	65	8028403011463
SILENT K30 T5,5	SLOM701SHA203	K30	3	5,5/4,0	2	13/189	YES	650	472/16,7	400/50	168/396,6	850x620x1100	65	8028403011470
SILENT K30 T5,5 SD	SLOM705SHA204	K30	3	5,5/4,0	2	13/189	YES	650	472/16,7	400/50	173/380,6	850x620x1100	65	8028403011487
SILENT K30 T7,5	SLOM801SHA205	K30	3	7,5/5,5	2	13/189	YES	800	582/20,6	400/50	182/400	850x620x1100	65	8028403011494
SILENT K30 T7,5 SD	SLOM805SHA206	K30	3	7,5/5,5	2	13/189	YES	800	582/20,6	400/50	187/411,4	850x620x1100	65	8028403011500
SILENT K50 T10	SMOM901SHA207	K50	3	10/7,5	2	13/189	YES	800	857/30,3	400/50	220/484	850x620x1100	68	8028403011517
SILENT K50 T10 SD	SMOM905SHA208	K50	3	10/7,5	2	13/189	YES	800	857/30,3	400/50	225/495	850x620x1100	68	8028403011524