

Technical data and accessories



Technical data

Wetrok Monomatic	LS	I	DS	HS	US
Item No.	20.051	20.053	20.055	20.057	20.059
Mains connection	230/50 V/Hz	230/50 V/Hz	230/50 V/Hz	230/50 V/Hz	230/50 V/Hz
Brush speed	162 1/min	120 1/min	170/340 1/min	400 1/min	1100 1/min
Power	1200 W	1600 W	1500 W	1500 W	1800 W
Torque	55 Nm	95 Nm	51/28.5 Nm	28.5 Nm	15.5 Nm
Working width	430 mm	430 mm	430 mm	430 mm	500 mm
Weight incl. pad drive disc (PAS)	34 kg	43 kg	35 kg	34 kg	45 kg
Access height (incl. PAS and pad)	100 mm	100 mm	100 mm	100 mm	–
Height above motor (incl. PAS and pad)	350 mm	350 mm	350 mm	350 mm	350 mm
Mains cable length	12.5 m	12.5 m	12.5 m	12.5 m	20.5 m
Transport wheels	Ø 160 mm	Ø 160 mm	Ø 160 mm	Ø 160 mm	Ø 160 mm
Protection rating	I	I	I	I	I
Noise level	57 dB	57 dB	51 dB	58 dB	56 dB

Method

Spray cleaning	•	•	•	(•)	
Polishing			•	•	•
Dry scrubbing	•	•	•	•	
Sanding, wet or dry	•	•			
Wet scrubbing	•	•	•		
Carpet pad method	•	•	(•)		
Wet shampooing	•	•	•		

• recommended (•) possible use

Accessories

Item No. 21.016 Spray unit 2 I
Item No. 21.001 Water tank 14 l

Item No. 21.025 Suction ring complete HS
Item No. 21.030 Suction ring complete US
Item No. 40.312 Suction unit
Item No. 21.022 Apparatus socket for suction unit

Item No. 21.112 Pad drive disc LS
Item No. 21.120 Pad drive disc HS
Item No. 21.126 Pad drive disc HS-PUR
Item No. 21.115 Pad drive disc for carpet pad

Item No. 24.758 Base plate (5 kg)
Item No. 21.160 Additional weight (1.9 kg)

Item No. 21.210 Union polishing brush
Item No. 21.270 Polypropylene scrubbing brush
Item No. 21.285 Super-nylon scrubbing brush
Item No. 21.295 Scrubbing brush for washed concrete
Item No. 21.300 Tynex scrubbing brush
Item No. 21.310 Nylon shampooing brush
Item No. 21.315 Hard nylon shampooing brush
Item No. 21.350 Sanding disc wood
Item No. 22.321 Poly-pad beige (yellow)
Item No. 22.322 Poly-pad red
Item No. 22.325 Poly pad blue
Item No. 22.323 Poly pad green
Item No. 22.324 Poly pad black
Item No. 22.334 Poly pad blue ice
Item No. 52.408 Microsol fibre pad
Item No. 22.330 Carpet pad
Item No. 22.401 Sanding sheet (SB) No. 16
Item No. 22.409 Sanding sheet (SB) No. 40
Item No. 22.411 Sanding net (SN) No. 60
Item No. 22.413 Sanding net (SN) No. 80
Item No. 22.415 Sanding net (SN) No. 100
Item No. 22.417 Sanding net (SN) No. 150
Item No. 22.338 Ultraspeed pad yellow
Item No. 22.339 Ultraspeed pad pink
Item No. 22.335 Ultraspeed pad blue ice

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten
Tel +41 43 255 51 51, Fax +41 43 255 51 52, www.wetrok.ch

Wetrok Ltd. Unit 4, Easter Court, Europa Boulevard,
Warrington, GB-Cheshire WA5 7ZB
Tel +44 1925 711222, Fax +44 1925 711333, www.wetrok.uk.com

Wetrok GmbH Maybachstrasse 35, D-51381 Leverkusen
Tel +49 2171 398-0, Fax +49 2171 398-100, www.wetrok.de

Wetrok AB Staffans väg 6 B, 3 tr, SE-192 78 Sollentuna
Tel +46 8 444 34 00, Fax +46 8 444 34 01, www.wetrok.se

Wetrok Polska S.A. ul. Łączyny 4 b, PL-02-820 Warszawa
Tel +48 22 331 20 50, Fax +48 22 331 20 60, www.wetrok.pl

wetrok[®]

© Copyright by Wetrok AG, Printed in Switzerland, 25/08/2008, 2000, Art.Nr. 63.029



consulting concept know-how **equipment** products academy service

Wetrok Monomatic

wetrok[®]

Turn up the power! With our new Monomatic single-disc machines

Come first in the cleaning race every time – with Wetrok's new range of single-disc machines! Functional design and high performance ensure optimum manoeuvrability: the machine's profile enables it to manoeuvre under low objects, it starts easily due to high startup speed, is convenient to handle due to optimum weight distribution and is perfectly equipped for all types of use. Each model is ideally designed to ensure an unparalleled driving experience for both men and women – whether for scrubbing washed concrete with the Monomatic I, or high-gloss polishing large areas with the Monomatic Ultraspeed.



1



2



3



Advantages of the Wetrok Monomatic

- Low profile ensures efficient cleaning under low objects
- Extended deployment range as the result of increased motor performance
- Ergonomic operation due to optimum weight distribution and continuously adjustable shaft
- Reduced maintenance costs due to corrosion-proof materials

1 Highest degree of efficiency with low clearance Monomatic fits into tight spaces – no need to interrupt your work flow. Simple to clean under objects as low as 10 cm, such as radiators, shelving and tables. Avoid difficult manual cleaning and achieve best results in the shortest possible time.

2 «Power-Start» and constant turning power for a wide range of uses Washed concrete, industrial flooring, granite? No problem for the Monomatic – it is accustomed to heavy-duty cleaning and cleans effortlessly even on highly irregular floor surfaces, thanks to its high startup speed. The Monomatic runs flawlessly once switched on. Let the Monomatic's turning power inspire you!

3 Optimum weight distribution ensures fatigue-free, ergonomic operation The Monomatic is designed so that the weight is located where it's needed – as low as possible and close to the brush or pad drive disc. The machine is balanced in optimum fashion, ensuring that it operates smoothly and quietly. This makes for easier cleaning and ensures perfect cleaning results.

High quality for regular, heavy-duty cleaning use Corrosion-proof materials ensure prolonged machine life and tried-and-tested Wetrok quality: Swiss made.